

FWP U3_ACK

OKN / FW / FWP

Insulated access roof light (right opening) featuring new design and option to change the opening side. It comes with the U3 single chamber energy-efficient glazing unit. Designed for all heated rooms.



Features



thermoPro



Window construction

Window colour	Pinewood, clear acrylic lacquer
Window flashing colour	Szarobrązowy RAL 7022
Window material	Aluminium
Number of seals [pcs.]	3
Material	Pinewood, vacuum impregnated
Air inlet	no
Roof type	Pitched (15° - 55°)
Material	Wood
Construction type	Access hatch

Installation

Kit / assembly	Window
Installation	• j; • n; • v;
Installation - versions	Battens

Control

Control method	Manually opened - handle
Solar powered	No

Detailed dimensions

Code	Commercial size	Window width (S) [mm]	Window height (L) [mm]
87AN01	55x78	547	781
87AN02	55x98	547	981
87AN03	66x98	657	981
87AN04	66x118	657	1181
87AN05	78x98	777	981
87AN06	78x118	777	1181
87AN07	78x140	777	1401
87AN08	94x118	937	1181
87AN09	94x140	937	1401
87AN13	78x160	777	1601
87AN15	94x98	937	981
87AN16	55x118	547	1181
87AN22	66x78	657	781
87AN80	94x160	937	1601

Technical parameters

Heat transfer coefficient Uw [W/m²K]	1.3
Tightness class (air permeability)	Class 3
Waterproofness	9A
Wind load resistance	Class C4
Reaction to fire	npd
Acoustics Rw [dB]	33
Acoustics Ra1 [dB]	32
AcousticsRa2 [dB]	27

Equipment / appearance

Number of paint layers	2
Paint color	natural
Paint type	Acrylic

Opening

Opening method	side - right
----------------	--------------

Code	Commercial size	Minimum roof pitch	Maximum roof pitch
87AN01	55x78	15°	55°
87AN02	55x98	15°	55°
87AN03	66x98	15°	55°
87AN04	66x118	15°	55°
87AN05	78x98	15°	55°
87AN06	78x118	15°	55°
87AN07	78x140	15°	55°
87AN08	94x118	15°	55°
87AN09	94x140	15°	55°
87AN13	78x160	15°	55°
87AN15	94x98	15°	55°
87AN16	55x118	15°	55°
87AN22	66x78	15°	55°
87AN80	94x160	15°	55°

