

Installation

## TECHNICAL SPECIFICATION EHV-P-G\_EC4

KOL / E / H



A sealing collar that allows a tight connection between a window and profiled roofing materials such as tiles, high profile sheeting. It can be used for roof coverings with a profile height of up to 90 mm.

Designed for balcony window installation.

Lead apron.

## **Component parts**

Maximum height of roof covering material profile [mm]	90		<ul> <li>standard upper element;</li> <li>standard lead apron;</li> </ul>
Window installation depth	V (0)	Main component parts	<ul> <li>standard right side;</li> <li>standard left side;</li> </ul>
Minimum slope angle [°]	15		<ul> <li>frame side covering profiles_standard;</li> </ul>
Maximum slope angle [°]	90		water drainage gutter;
Material			<ul> <li>roof rails;</li> <li>installation set;</li> </ul>
Sheet thickness [mm]	0,6		<ul><li>hooks;</li><li>fitting instructions;</li></ul>
Flashing material	Aluminium sheet metal RAL 7022	Module type	<ul> <li>basic flashing;</li> </ul>
Apron		Others	
Apron material	Lead apron	Roof covering type	<ul> <li>high profile up to 90 mm or 120 mm (H);</li> </ul>
		Flashing destination	<ul> <li>for balcony window;</li> </ul>